

Shenzhen Feasycom Technology Co.,LTD

www.feasycom.com

Address: Rm 2004-2005, 20F, Huichao Technology Bldg, Jinhai Rd, Xixiang, Baoan Dist, Shenzhen, 518100, China.

Tel: 86-755-23062695

FSC-BP104

Bluetooth 5.0 Battery Powered Beacon

Datasheet Version 1.4



FeasyBeacon 5Mart adopting the TI CC2640R2F Chipset, the newest bluetooth 5.0 low energy technology, with 5 year super long work life guaranteed via high quality AAA battery. Transmit distance reach up to 500m.

With multi-functional FeasyBeacon APP (Android & iOS),providing 10 slots broadcast advertising frames ,it simultaneously supports iBeacon, Eddystone (URL and UID), AltBeacon.

With battery-powered method, easy for installation, anyway, anytime, it's the ideal choice for stable or temporary installations, such as shops, museums, exhibits, trade fairs, retails, stadium, asset identification, restaurant, etc.



Beacon Version User-configurable characteristics UUID, major and minor numbers, tx power at 1m characteristics Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Beacon on/off AlfiBeacon Version User-configurable UUID, major and minor numbers, tx power at 1m characteristics UUI	Advertising		
UID, major and minor numbers, tx power at 1m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch iBeacon or/off AllBeacon Version User-configurable characteristics Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable With 1			
characteristics Advertising interval Secure config Albeacon Version User-configurable Characteristics Advertising interval Secure config Albeacon Version User-configurable Characteristics Advertising interval UUD, major and minor numbers, tx power at 1m Albeacon Version User-configurable Characteristics Advertising interval Secure config Albeacon onoff Albeacon onoff Albe			
Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Beacon on/off AttBeacon Version Beacon on/off User-configurable characteristics UUID,major and minor numbers, tx power at 1m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch AltBeacon on/off Eddystone Version User-configurable User-configurable characteristics UID Frame, URL Frame, bx power at 0m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone Version Secure config access password, connectable/ non-connectable Switch Eddystone Version Product Specification Chipset TI CC2640R2F Standard Bit to 1.2 sec (programmable, with 0.1 sec steps) Max Number of Broadcast TI CC2640R2F Standard Bit to 2.4 sec steps) Max Population Code Default		UUID,major and minor numbers, tx power at 1m	
Secure conflig access password, connectable/ non-connectable Switch Beacon on/off AllBeacon Version User-configurable characteristics Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch AltBeacon on/off Eddystone Version USER Frame, URL Frame, IX power at 0m User-configurable characteristics UID Frame, URL Frame, IX power at 0m Advertising interval 0.1 to 1.2 sec (programmable with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Eddystone on/off Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system 10 S 7.0 + Android4.3 + Android /		0.1 to 1.2 sec (programmable with 0.1 sec steps)	
Switch IBBacon on/oilf AIRBacon Version UUID,major and minor numbers, tx power at 1m characteristics Advertising interval 0.1 to 1.2 sec (programmable,with 0.1 sec steps) Secure conflig access password, connectable/ non-connectable Switch AltBeacon on/off Eddystone Version UDF rame, URL Frame, tx power at 0m User-confligurable characteristics UID Frame, URL Frame, tx power at 0m Advertising interval 0.1 to 1.2 sec (programmable,with 0.1 sec steps) Secure conflig access password, connectable/ non-connectable Switch Eddystone on/off Foduct Specification TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Stots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system IOS 7.0+ Android4.3+ Android /IOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) <tr< td=""><td>-</td><td></td></tr<>	-		
AllBeacon Version User-configurable characteristics Advertising interval Secure config	-		
User-configurable characteristics Advertising interval Secure config Caces password, connectable/ non-connectable Switch AllBeacon on/off Eddystone Version User-configurable characteristics Advertising interval User-configurable characteristics UID Frame, URL Frame, tx power at 0m Characteristics UID Frame, URL Frame, tx power at 0m Characteristics Advertising interval Secure config Caces password, connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast APP Configuration Code Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AitBeacon adv at the same time TX power Support system OTA (over the air update firmware), support iBeacon and Eddystone, AitBeacon adv at the same time TX power SdBm (Max) Power SdBm (Max) Power Range 10S 7.0+Android4.3+ Android / 10S config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Gain Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Gain Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Gain Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Gain Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Addis (Max) Power Supply Built-in Battery Battery Type PCB F shape antenna Addis (Max) Power Supply Battery Type PCB F shape antenna Addis (Max) Power Supply Battery Type PCB F shape antenna Addis (Max) Power Supply Battery Type PCB F shape antenna Addis (Max) Power Supply Battery Life PCB F shape antenna Addis (Max) PCB F shape antenna Addis (Max) PCB			
characteristics Advertisting interval Advertishing interval Secure config Connectable/ non-connectable/ non-connectable/ Switch AttBeacon on/off Eddystone Version User-configurable characteristics UID Frame, URL Frame, tx power at 0m Advertishing interval Secure config Connectable/ non-connectable/ Description UID Frame, URL Frame, tx power at 0m Advertishing interval Connectable/ non-connectable/ Description Connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset Ti CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power SdBm (Max) Power Range 10 T-23 + 5 dBm Support system 10 S7.0+Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type POB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2'YAA(LRO3) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Packing Size Net weight Protection IP40			
Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch AttBeacon on/off Eddystone Version UDF Frame, URL Frame, tx power at 0m User-configurable characteristics UID Frame, URL Frame, tx power at 0m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Ugrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time Xx power 5dBm (Max) Power Range -23 + 5 dBm Support system iOS 7.0+, Android 4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max)		UUID,major and minor numbers, tx power at 1m	
Secure config access password, connectable/ non-connectable Switch AltBeacon on/off Eddystone Version User-configurable characteristics Characteristics UID Frame, URL Frame, tx power at 0m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Till CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range 2-3 - 5 dBm Support system i0S 7.0+, Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Suply Buttery Life Up to 5 years(ADV Interval: 1280ms; TX Power = 0dBm) <		0.1 to 1.2 sec (programmable with 0.1 sec steps)	
Switch AltBeacon on/off Eddystone Version User-configurable characteristics UID Frame, URL Frame, Ix power at 0m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range 23 - +5 dBm Support system IOS 7.0+ Android4.3+ Android / IOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms; TX Power= 0dBm)			
Eddystone Version User-configurable characteristics UID Frame, URL Frame, tx power at 0m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system iOS 7.0+, Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic	-	·	
UID Frame, URL Frame, tx power at 0m Advertising interval 0.1 to 1.2 sec (programmable,with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power SdBm (Max) Power Range -23 -+ 5 dBm Support system Support system Possy FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Type 3*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
characteristics UID Frame, URL Frame, tx power at 0m Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system IOS 7.0+, Android4.3+ Android / IOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable	-		
Advertising interval 0.1 to 1.2 sec (programmable, with 0.1 sec steps) Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time Xx power 5dBm (Max) Power Range -23 - 45 dBm Support system IOS 7.0+,Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LRO3) (Battery not included) Battery Type 2*AAA(LRO3) (Battery not included) Battery Life Up to 5 years (ADV Interval: 1280ms; TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable<		UID Frame, URL Frame, tx power at 0m	
Secure config access password, connectable/ non-connectable Switch Eddystone on/off Product Specification TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system iOS 7.0+, Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms; TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size 461mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection <		0.1 to 1.2 sec (programmable with 0.1 sec steps)	
Switch Eddystone on/off Product Specification TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system IOS 7.0+, Android4.3+ Android / IOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system iOS 7.0+,Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
Chipset TI CC2640R2F Standard Bluetooth 5.0 Max Number of Broadcast 10 Slots configurable APP Configuration Code Default Pin Code: 000000 Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power 5dBm (Max) Power Range -23 - +5 dBm Support system iOS 7.0+,Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Ф61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
StandardBluetooth 5.0Max Number of Broadcast10 Slots configurableAPP Configuration CodeDefault Pin Code: 000000Upgrade ModeOTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same timeTX power5dBm (Max)Power Range-23 - +5 dBmSupport systemiOS 7.0+, Android4.3+Android / iOS config appFeasyBeacon(Free for lifetime using)Work distanceUp to 500m(open area)TypePCB F shape antennaGain3dBi (Max)Power SupplyBuilt-in BatteryBattery Type2*AAA(LR03) (Battery not included)Battery LifeUp to 5 years(ADV Interval: 1280ms;TX Power= 0dBm)MaterialABS plasticColorWhite, Blue, can be customizableSize\$461mm, H:18mmPacking Size\$90*105*30mmNet weight46.2gProtectionIP40		TLCC2640R2F	
Max Number of Broadcast10 Slots configurableAPP Configuration CodeDefault Pin Code: 000000Upgrade ModeOTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same timeTX power5dBm (Max)Power Range-23 - +5 dBmSupport systemiOS 7.0+,Android4.3+Android / iOS config appFeasyBeacon(Free for lifetime using)Work distanceUp to 500m(open area)TypePCB F shape antennaGain3dBi (Max)Power SupplyBuilt-in BatteryBattery Type2*AAA(LR03) (Battery not included)Battery LifeUp to 5 years(ADV Interval: 1280ms;TX Power= 0dBm)MaterialABS plasticColorWhite, Blue, can be customizableSizeФ61mm, H:18mmPacking Size90*105*30mmNet weight46.2gProtectionIP40	-		
APP Configuration Code Upgrade Mode OTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same time TX power SdBm (Max) Power Range -23 - +5 dBm Support system iOS 7.0+,Android4.3+ Android / iOS config app Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Ф61mm, H:18mm Packing Size Protection Protection			
Upgrade ModeOTA (over the air update firmware), support iBeacon and Eddystone, AltBeacon adv at the same timeTX power5dBm (Max)Power Range-23 - +5 dBmSupport systemiOS 7.0+,Android4.3+Android / iOS config appFeasyBeacon(Free for lifetime using)Work distanceUp to 500m(open area)TypePCB F shape antennaGain3dBi (Max)Power SupplyBuilt-in BatteryBattery Type2*AAA(LR03) (Battery not included)Battery LifeUp to 5 years(ADV Interval: 1280ms;TX Power= 0dBm)MaterialABS plasticColorWhite, Blue, can be customizableSizeΦ61mm, H:18mmPacking Size90*105*30mmNet weight46.2gProtectionIP40			
TX power SdBm (Max) Power Range -23 - +5 dBm Support system iOS 7.0+,Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
Power Range -23 - +5 dBm Support system iOS 7.0+,Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
Support system iOS 7.0+,Android4.3+ Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Ф61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40	·		
Android / iOS config app FeasyBeacon(Free for lifetime using) Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight Protection IP40			
Work distance Up to 500m(open area) Type PCB F shape antenna Gain 3dBi (Max) Power Supply Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Ф61mm, H:18mm Packing Size 90*105*30mm Net weight Protection IP40			
Type PCB F shape antenna Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Ф61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40		, , , , , , , , , , , , , , , , , , ,	
Gain 3dBi (Max) Power Supply Built-in Battery Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40	Type		
Power Supply Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Ф61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40		·	
Battery Type 2*AAA(LR03) (Battery not included) Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40	Power Supply		
Battery Life Up to 5 years(ADV Interval: 1280ms;TX Power= 0dBm) Material ABS plastic Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
MaterialABS plasticColorWhite, Blue, can be customizableSizeΦ61mm, H:18mmPacking Size90*105*30mmNet weight46.2gProtectionIP40			
Color White, Blue, can be customizable Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40	-		
Size Φ61mm, H:18mm Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
Packing Size 90*105*30mm Net weight 46.2g Protection IP40			
Net weight 46.2g Protection IP40			
Protection IP40			
	-		
Operating temperature -20°C to +60°C	Operating temperature	-20°C to +60°C	